



RAVENOL RNF SAE 0W-20



1L | 1111153-001

4L | 1111153-004

5L | 1111153-005

20L | 1111153-B20

208L | 1111153-208

Kategorie: Passenger car motor oil

Artikelnummer: 1111153

Viscosity: 0W-20

Specification: ACEA C5

Oil type: Synthetic

Approvals: Renault RN17FE

Application: Passenger car

Technology: Clean Synto®

RAVENOL RNF SAE 0W-20 is a synthetic low-friction motor oil with CleanSynto® technology for passenger car petrol and diesel engines based on the latest additive technology with selected base oils. It was specially developed for Renault and Dacia engines.

RAVENOL RNF SAE 0W-20 is suitable for use in petrol and diesel engines with and without a particle filter and exhaust gas catalytic converter and in engines according to the latest EURO 6d-Temp standard. The viscosity range SAE 0W-20 ensures a reliable cold start at low outside temperatures and full lubricity at high operating temperatures. Frictional losses and wear are reduced.

By significantly reducing fuel consumption, **RAVENOL RNF SAE 0W-20** helps to protect the environment by reducing emissions.

Extended oil change intervals according to the manufacturer's instructions.

Application Note

RAVENOL RNF SAE 0W-20 is suitable for all petrol engines, diesel engines without DPF (Diesel Particulate Filter), diesel engines with DPF from EURO 6d-Temp by RENAULT and Dacia as well as for diesel engines with DPF, if an engine oil according to ACEA C5-16 required.

RAVENOL RNF SAE 0W-20 can be used universally in all petrol and diesel engines with and without turbocharging. It can also be used for the latest EURO 6d engines.

The oil change intervals according to the manufacturer's instructions must be observed.

Characteristics

- low content of ash-forming components (sulfate ash, phosphorus and sulfur)
- specific additive technology for optimal lubrication
- extremely high aging resistance, durability and robustness
- excellent cleaning properties
- Fuel savings

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C		841,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C		8,3	DIN 51562-1
Viscosity at 40 °C		38,8	DIN 51562-1
Viscosity Index VI		199	DIN ISO 2909
HTHS Viscosity at 150 °C		2,75	ASTM D5481
CCS Viscosity at -35 °C		4800	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -40 °C		17300	ASTM D4684
Pourpoint		-48	DIN ISO 3016
Noack Volatility		10,9	ASTM D5800
Flashpoint		232	DIN EN ISO 2592
tbn		8,7	ASTM D2896
Sulphated Ash		0,79	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.