



RAVENOL Super Turbo SAE 20W-50



1L | 1113126-001

4L | 1113126-004

5L | 1113126-005

10L | 1113126-010

20L | 1113126-020

20L | 1113126-B20

60L | 1113126-060

60L | 1113126-D60

208L | 1113126-208

208L | 1113126-D28

1000L | 1113126-700

Kategorie: Passenger car motor oil

Artikelnummer: 1113126

Viscosity: 20W-50

Specification: ACEA A3/B4, ACEA E2, API CF, API CH-4, API SL

Oil type: Mineral

Recommendation: Cummins CES 20071, Deutz DQC II-10, Mack EO-M, MAN 271, MB 228.1, MB 229.1, MTU Typ 1, VOLVO VDS, VW 501 01, VW 505 00

Application: Passenger car

RAVENOL SUPER TURBO SAE 20W-50 is a universal multigrade engine oil for passenger car gasoline and diesel engines with or without turbocharging. Excellent Features by special solvent refined base oils and special additives. Minimizes friction and wear, good cold start properties. Extended oil change intervals according to manufacturer instructions.

The high additive content of **RAVENOL SUPER TURBO SAE 20W-50** guarantees an excellent effect, especially in regard to the detergent, dispersant and anti-wear properties.

RAVENOL SUPER TURBO SAE 20W-50 is a top product with high safety reserves.

Application Note

RAVENOL SUPER TURBO SAE 20W-50 is used in passenger car gasoline and diesel engines with and without turbocharging, if the SAE 20W-50 is required.

RAVENOL SUPER TURBO SAE 20W-50 is miscible with all HD motor oils based on mineral oil.

Characteristics

- Excellent detergent and dispersant
- A good cold start performance
- High oxidation stability
- An excellent viscosity-temperature behaviour
- Best wear protection
- High safety reserves
- Reduction of emissions
- Catalyst suitability

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C		876,0	EN ISO 12185
Colour		braun	VISUELL
Viscosity at 100 °C	mm ² /s	18,9	DIN 51562-1
Viscosity at 40 °C	mm ² /s	161,2	DIN 51562-1
Viscosity Index VI		133	DIN ISO 2909
CCS Viscosity at -15 °C	mPa*s	6500	ASTM D5293
Pourpoint	°Celsius	-30	DIN ISO 3016
Flashpoint	°Celsius	241	DIN EN ISO 2592
tbn	mgKOH/g	11,3	ASTM D2896

All indicated data are approximate values and are subject to the commercial fluctuations.