



RAVENOL Regular 30

Kategorie: Oltimer engine oil (Classic products)

Artikelnummer: 1113302

Viscosity: 30

Specification: API SA

Oil type: Mineral

Application: Passenger car, Hobby and garden



RAVENOL Motorenoel SAE 30 W Regular is a non-alloyed engine oil, it is manufactured using carefully selected pure mineral raffinates. It provides oxidation stability, it is non-foaming and also has excellent viscosity-temperature characteristics. Thanks to its low setting point, this oil can be used in both low and high temperatures and guarantees perfect lubrication.

Application Note

RAVENOL Motorenoel SAE 30 W Regular SA is used in passenger car petrol and diesel engines where the API specification SA is required.

20L | 1113302-020

20L | 1113302-B20

60L | 1113302-060

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		braun	VISUELL
Viscosity at 100 °C	mm ² /s	11,0	DIN 51562-1
Viscosity at 40 °C	mm ² /s	92,0	DIN 51562-1
Viscosity Index VI		105	DIN ISO 2909
Density at 20 °C	kg/m ³	882,0	EN ISO 12185
Flashpoint	°C	245	DIN EN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.