



RAVENOL Spezial Diesel SAE 15W-40



Kategorie: Truck engine oil

Artikelnummer: 1113311

Viscosity: 15W-40

Specification: ACEA B2, API CD

Oil type: Mineral

Recommendation: CCMC G4, MB 227.1, MIL-L-2104 D, MIL-L-46152 B

Application: Passenger car, Truck, Agricultural machinery, Hobby and garden

RAVENOL Spezial Diesel SAE 15W-40 is excellent multi-grade special engine oil which can be used in passenger cars as well as trucks. It fulfils the requirements of modern Diesel engines with or without supercharging. The favorable viscosity range ensures year-round high lubricity under different operating conditions.

Application Note

RAVENOL Spezial Diesel SAE 15W-40 can be used according to the manufacturer specification for Dieselenigines.

Characteristics

- A good shear stability
- A high oxidation stability
- An excellent viscosity temperature behaviour
- Convincing detergent and dispersant attributes
- High security reserves even under limited lubrication conditions
- Very good cold start attributes
- Avoids the formation of accumulations of mud (black sludge)
- No problems with the use in catalyst vehicles

1L | 1113311-001

4L | 1113311-004

5L | 1113311-005

20L | 1113311-020

20L | 1113311-B20

60L | 1113311-060

208L | 1113311-208

1000L | 1113311-700

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	865,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	14,1	DIN 51562-1
Viscosity at 40 °C	mm ² /s	106,1	DIN 51562-1
Viscosity Index VI		135	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	240	DIN EN ISO 2592
tbn	mg KOH/g	7,1	ASTM D2896
Sulphated Ash	%wt.	0,9	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.