



RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40



1L | 1115100-001
5L | 1115100-005
20L | 1115100-020
60L | 1115100-060
60L | 1115100-D60
208L | 1115100-208

Kategorie: Passenger car motor oil

Artikelnummer: 1115100

Viscosity: 5W-40

Specification: ACEA A3/B4, API SN Plus, API SP

Oil type: Synthetic

Recommendation: BMW Longlife-01, MB 229.5, Opel/GM-LL-B-025, Porsche A40, Renault RN0700, Renault RN0710, VW 502 00, VW 505 00

Application: Passenger car

The synthetic motor oil **RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40** is a new development with a unique formula specifically for high mileage vehicles of approx. 100,000 km and more.

RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40 is particularly recommended for vehicles with high mileage petrol and diesel engines with and without turbocharge and direct injection.

The extremely conditioning and cleaning agents in **RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40** revitalise critical engine parts and particularly protect gaskets. This can extend the life, particularly in older vehicles with high mileage.

RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40 features outstanding lubrication and excellent shear stability, and the added conditioners simultaneously reduce oil consumption and protect from sludge and wear.

Application Note

RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40 is perfectly suited for year-round use in high mileage petrol and diesel engines with 100,000 km and more, and promotes low oil consumption. A very clean engine is guaranteed.

RAVENOL SVS Standard Viscosity Synto Oil SAE 5W-40 extends the life of the engine in older vehicles by reducing oil consumption and protecting from sludge and wear. A very clean engine is guaranteed.

Characteristics

- High wear protection
- Fuel saving because of easy running characteristics
- Outstanding detergent and dispersant properties prevent sludge
- High oxidation stability for a long life
- Brilliant cold cranking behaviour
- Excellent viscosity-temperature behaviour
- Low vaporisation characteristics, therefore reduced oil consumption
- Suitable for catalytic converters

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	847,0	EN ISO 12185
Colour		braun	VISUELL
Viscosity at 100 °C	mm ² /s	13,3	DIN 51562-1
Viscosity at 40 °C	mm ² /s	78,2	DIN 51562-1
Viscosity Index VI		173	DIN ISO 2909
HTHS Viscosity at 150 °C	mPa*s	3,91	ASTM D5481
CCS Viscosity at -30 °C	mPa*s	5480	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	25.000	ASTM D4684
Pourpoint	°C	-42	DIN ISO 3016
Noack Volatility	% M/M	8,7	ASTM D5800
Flashpoint	°C	240	DIN EN ISO 2592
tbn	mg KOH/g	12,0	ASTM D2896
Sulphated Ash	%wt.	1,19	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.