



RAVENOL HVP High Viscosity Perform. Oil SAE 15W-50



1L | 1116104-001
5L | 1116104-005
10L | 1116104-010
20L | 1116104-020
20L | 1116104-B20
60L | 1116104-060
208L | 1116104-208
208L | 1116104-D28

Kategorie: Passenger car motor oil

Artikelnummer: 1116104

Viscosity: 15W-50

Specification: ACEA A3/B4, API CF, API SN

Oil type: Semi-synthetic

Recommendation: MB 229.1

Application: Passenger car

RAVENOL HVP High Viscosity Performance Oil SAE 15W-50 is particularly recommended for vehicles with high mileage, petrol and diesel engines, with and without turbocharge and direct injection.

The semi-synthetic motor oil **RAVENOL HVP High Viscosity Performance Oil SAE 15W-50** is developed with a unique formula specifically for high mileage vehicles of approx. 100,000 km and more.

The extremely conditioning and cleaning additives in **RAVENOL HVP High Viscosity Performance Oil SAE 15W-50** revitalize critical engine parts and particularly protect gaskets. This can extend the life, particularly in older vehicles with high mileage.

RAVENOL HVP High Viscosity Performance Oil SAE 15W-50 features outstanding lubrication and excellent shear stability, and the added conditioners simultaneously reduce oil consumption and protect from sludge and wear.

Application Note

RAVENOL HVP High Viscosity Performance Oil SAE 15W-50 is perfectly suited for year-round use in high mileage petrol and diesel engines with 100,000 km and more, and promotes low oil consumption. A very clean engine is guaranteed.

RAVENOL HVP High Viscosity Performance Oil SAE 15W-50 extends the life of the engine in older vehicles by reducing oil consumption and protecting from sludge and wear. A very clean engine is guaranteed.

Characteristics

- High wear protection
- Outstanding detergent and dispersant properties prevent sludge
- Low vaporisation characteristics, therefore reduced oil consumption
- High oxidation stability for a long life
- Brilliant cold cranking behaviour through special additives
- Excellent viscosity-temperature behaviour
- Suitable for catalytic converters

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	866,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	18,7	DIN 51562-1
Viscosity at 40 °C	mm ² /s	139,1	DIN 51562-1
Viscosity Index VI		152	DIN ISO 2909
CCS Viscosity at -20 °C	mPa*s	5710	ASTM D5293
Pourpoint	°C	-30	DIN ISO 3016
Flashpoint	°C	242	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.