



RAVENOL SVP Stand. Viscos. Perform. Oil SAE 15W-40



1L | 1117100-001
4L | 1117100-004
5L | 1117100-005
10L | 1117100-010
20L | 1117100-020
20L | 1117100-B20
60L | 1117100-060
208L | 1117100-208

Kategorie: Passenger car motor oil

Artikelnummer: 1117100

Viscosity: 15W-40

Specification: ACEA A3/B4, API CF, API SJ

Oil type: Mineral

Recommendation: MAN 271, MB 229.1, VW 505 00, ZF TE-ML 07C

Application: Passenger car

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 is particularly recommended for vehicles with high mileage petrol and diesel engines with and without turbocharge and direct injection. The mineral motor oil **RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40** is a new development with a unique formula specifically for high mileage vehicles of approx. 100,000 km and more.

The extremely conditioning and cleaning agents in **RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40** revitalise critical engine parts and particularly protect gaskets. This can extend the life, particularly in older vehicles with high mileage.

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 features outstanding lubrication and excellent shear stability, and the added conditioners simultaneously reduce oil consumption and protect from sludge and wear.

Application Note

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 is perfectly suited for year-round use in high mileage petrol and diesel engines with 100,000 km and more, and promotes low oil consumption. A very clean engine is guaranteed.

RAVENOL SVP Standard Viscosity Performance Oil SAE 15W-40 extends the life of the engine in older vehicles by reducing oil consumption and protecting from sludge and wear. A very clean engine is guaranteed.

Characteristics

- High wear protection, important for large mileages and inadequate oil changes
- Outstanding detergent and dispersant properties prevent sludge
- High oxidation stability for a long life
- Brilliant cold cranking behaviour through special additives
- Excellent viscosity-temperature behaviour
- Low vaporisation characteristics, therefore reduced oil consumption
- Suitable for catalytic converters

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		gelbbraun	VISUELL
Density at 20 °C		873	EN ISO 12185
Viscosity at 40 °C		107,2	DIN 51562-1
Viscosity at 100 °C		14,4	DIN 51562-1
Viscosity Index VI		137	DIN ISO 2909
Pourpoint		-36	DIN ISO 3016
Flashpoint (CC)		240	DIN EN ISO 2592
tbn		8,9	ASTM D2896
Sulphated Ash		1,1	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.