



RAVENOL Oldtimer Classic SAE 30 API SB



1L | 1118113-001
5L | 1118113-005
20L | 1118113-020
60L | 1118113-060

Kategorie: Oldtimer engine oil (Classic products)

Artikelnummer: 1118113

Viscosity: 30

Specification: API SB

Oil type: Mineral

Application: Oldtimer

With their unique formulation, **RAVENOL Classic 1 Engine Oils** extend the service life of engines in older vehicles by offering protection against sludge formation and wear and tear. By minimizing friction, fuel consumption is also reduced.

RAVENOL Oldtimer Classic SAE 30 API SB is an alloyed single grade engine oil for use in classic vehicles with or without an oil filter. It is manufactured using carefully selected pure mineral raffinates. It provides oxidation stability, it is non-foaming and also has excellent viscosity-temperature characteristics. Thanks to its low setting point, this oil can be used in both low and high temperatures and guarantees perfect lubrication. It is suitable for use in most petrol engines / classic vehicles built before 1951. Using this oil in modern engines can lead to defective performance or cause damage.

Application Note

RAVENOL Oldtimer Classic SAE 30 API SB is designed for use in the engines of vehicles which were built prior to 1951, where the API specification SB is required. Adhere to oil change intervals specified in the manufacturer's instructions.

Technical Product Data

| PROPERTY | UNIT | DATA | AUDIT |
|---------------------|--------------------|-------|-----------------|
| Density at 20 °C | kg/m ³ | 877,0 | EN ISO 12185 |
| Colour | | gelb | VISUELL |
| Viscosity at 100 °C | mm ² /s | 11,41 | DIN 51562-1 |
| Viscosity at 40 °C | mm ² /s | 103,3 | DIN 51562-1 |
| Viscosity Index VI | | 96 | DIN ISO 2909 |
| Pourpoint | °C | -12 | DIN ISO 3016 |
| Flashpoint | °C | 266 | DIN EN ISO 2592 |

All indicated data are approximate values and are subject to the commercial fluctuations.