



RAVENOL NDT Nord Duty Truck SAE 5W-40



1L | 1122103-001
5L | 1122103-005
10L | 1122103-010
20L | 1122103-020
20L | 1122103-B20
60L | 1122103-060
208L | 1122103-208
1000L | 1122103-700

Kategorie: Truck engine oil

Artikelnummer: 1122103

Viscosity: 5W-40

Specification: ACEA E7, ACEA E9, API CJ-4, API SM

Oil type: Full synthetic

Approvals: API CJ-4, API SM, Cummins CES 20081, Detroit Diesel Corporation (DDC) DFS93K218, Mack EO-O Premium Plus, Renault VI RLD-3, VOLVO VDS-4

Recommendation: Chrysler MS-10902, Detroit Diesel DDC 93K214, Detroit Diesel DDC 93K215, DTFR 15C100 (MB 228.31), Ford WSS-M2C171-E, MTU Typ 2

Application: Truck

RAVENOL NDT Nord Duty Truck SAE 5W-40 is a full synthetic all-season multi-grade engine oil based on PAO, which is used in heavy-duty diesel engines of commercial vehicles, pick-ups and SUVs.

RAVENOL NDT Nord Duty Truck SAE 5W-40 can be used in new low-emission engines with exhaust gas after-treatment.

RAVENOL NDT Nord Duty Truck SAE 5W-40 delivers reduced friction, wear and fuel consumption and ensures extended oil change intervals up to 80.000 km in turbo-diesel engines.

RAVENOL NDT Nord Duty Truck SAE 5W-40 improves engine performance, reliability and cleanness thanks to active agents that retain excellent viscosity.

Application Note

RAVENOL NDT Nord Duty Truck SAE 5W-40 is used in the viscosity grade SAE 5W-40 by engine manufacturers as an all-season, multi-grade engine oil in heavy duty diesel engines of commercial vehicles with exhaust gas after-treatment.

RAVENOL NDT Nord Duty Truck SAE 5W-4 is the preferred recommendation of manufacturers for turbo diesel engines due to the extended oil change intervals up to 80.000 km.

Characteristics

- an extremely high pressure absorption
- very high oxidation stability
- an excellent aging resistance
- outstanding viscosity temperature characteristics
- high safety reserves also under marginal lubricating conditions
- suitable for extended oil change intervals
- ideally suited for demanding operating conditions

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	849,0	EN ISO 12185
Colour		braun	VISUELL
Viscosity at 100 °C	mm ² /s	14,45	DIN 51562-1
Viscosity at 40 °C	mm ² /s	89,7	DIN 51562-1
Viscosity Index VI		167	DIN ISO 2909
HTHS Viscosity at 150 °C	mPa*s	3,87	ASTM D5481
CCS Viscosity at -30 °C	mPa*s	4957	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	20.200	ASTM D4684
Pourpoint	°C	-51	DIN ISO 3016
Noack Volatility	% M/M	8,9	ASTM D5800
Flashpoint	°C	234	DIN EN ISO 2592
tbn	mg KOH/g	10,1	ASTM D2896
Sulphated Ash	%wt.	0,91	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.