



RAVENOL Performance Truck SAE 10W-40



- 1L | 1122106-001
- 5L | 1122106-005
- 10L | 1122106-010
- 20L | 1122106-020
- 20L | 1122106-B20
- 60L | 1122106-060
- 60L | 1122106-D60
- 208L | 1122106-208
- 208L | 1122106-D28
- 1000L | 1122106-700

Kategorie: Truck engine oil

Artikelnummer: 1122106

Viscosity: 10W-40

Specification: ACEA E4/E7, API CF, API CI-4

Oil type: Semi-synthetic

Approvals: API CI-4, Deutz DQC III-10, DTFR 15B120 (MB 228.5), Mack EO-N, MAN M 3277, MTU Typ 3, Renault VI RLD-2, TEDOM 258-4 (61-0-0258), VOLVO VDS-3

Recommendation: Cummins CES 20076, Cummins CES 20077, Cummins CES 20078, DAF HP-1, DAF HP-2, DTFR 13D100 (MB 235.27), DTFR 13D110 (MB 235.28), Global DHD-1, JASO DH-1 (JASO M355:2000), Mack EO-M Plus, MB 228.5, MB 235.27, MB 235.28, Scania LDF-2, Voith Retarder B

Application: Truck

RAVENOL Performance Truck SAE 10W-40 is semi-synthetic multi-grade diesel engine oil for highly loaded diesel engines based on MC-systems.

RAVENOL Performance Truck SAE 10W-40 is low-friction long-life engine oil for all kind of diesel engines with and without turbocharging in trucks, buses and machinery. Suitable for the longest oil change intervals.

Application Note

RAVENOL Performance Truck SAE 10W-40 has a higher performance than conventional high-performance engine oils. International such oils are called UHPD oils (UHPD = Ultra High Performance Diesel Oil). Regardless of the particular mileage, older diesel engines on **RAVENOL Performance Truck SAE 10W-40** should be changed without rinsing.

Characteristics

- High wear protection even under constant load at full throttle
- Reduced fuel consumption by low-friction characteristics
- Quick oil circulation reduces cold-start and warm-up wear
- Protection against bore polishing of cylinder paths
- Reduction of exhaust particles
- Protects against corrosion, even when using diesel fuels with high sulfur content
- Safe protection against deposits and sticking, both under extreme thermal loads and short haul
- Optimum compatibility with seal materials
- Environmentally friendly due longest oil change intervals and low evaporation losses
- Guaranteed extended drain intervals for the long-haul truck or transport

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	866,0	EN ISO 12185
Colour		dunkelbraun	VISUELL
Viscosity at 100 °C	mm ² /s	14,5	DIN 51562-1
Viscosity at 40 °C	mm ² /s	96,2	DIN 51562-1
Viscosity Index VI		156	DIN ISO 2909
Pourpoint	°C	-33	DIN ISO 3016
Flashpoint	°C	234	DIN EN ISO 2592
tbn	mg KOH/g	13,2	ASTM D2896
Sulphated Ash	%wt.	1,7	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.