



RAVENOL Standard Truck SAE 30

RAVENOL Standard Truck SAE 30

20L | 1123620-020

20L | 1123620-B20

60L | 1123620-060

208L | 1123620-208

1000L | 1123620-700

Kategorie: Truck engine oil

Artikelnummer: 1123620

Viscosity: 30

Specification: API CF, API SF

Oil type: Mineral

Recommendation: Allison C4, Caterpillar TO-2, MAN 270, MB 227.0, MIL-L-2104 E, MTU Typ 1 (DDC BR 2000 und 4000), Voith DIWA, Voith Retarder A, ZF TE-ML 02C, ZF TE-ML 03B, ZF TE-ML 04B, ZF TE-ML 06A, ZF TE-ML 07D

Application: Truck

RAVENOL Standard Truck SAE 30 is mineral mono grade motor oil for trucks. It is an all-season oil for all truck diesel engine types.

RAVENOL Standard Truck SAE 30 offers high protection against friction and abrasion, excellent cold start characteristics. Extended oil change intervals according to manufacturer's recommendations.

Application Note

RAVENOL Standard Truck SAE 30 is mono grade motor oil for use in truck diesel engines. It is also suitable for stationary plants.

Characteristics

- Good shear stability
- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	887,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	11,6	DIN 51562-1
Viscosity at 40 °C	mm ² /s	102,3	DIN 51562-1
Viscosity Index VI		100	DIN ISO 2909
Pourpoint	°C	-27	DIN ISO 3016
Flashpoint	°C	262	DIN EN ISO 2592
tbn	mg KOH/g	13,0	ASTM D2896

All indicated data are approximate values and are subject to the commercial fluctuations.