



# RAVENOL Standard Truck SAE 40

**Kategorie:** Truck engine oil

**Artikelnummer:** 1123625

**Viscosity:** 40

**Specification:** API CF, API SF

**Oil type:** Mineral

**Recommendation:** Allison C4, Caterpillar TO-2, MAN 270, MB 227.0, MIL-L-2104 E, MTU Typ 1 (DDC BR 2000 und 4000), Voith DIWA, Voith Retarder A, ZF TE-ML 02C, ZF TE-ML 03B, ZF TE-ML 04B, ZF TE-ML 06A

**Application:** Truck

**RAVENOL Standard Truck SAE 40** is mineral mono grade motor oil for trucks. All-season oil for all truck diesel engine types. High protection against friction and abrasion, excellent cold start characteristics. Extended oil change intervals according to manufacturer's recommendations.



20L | 1123625-020

208L | 1123625-208

1000L | 1123625-700

## Application Note

**RAVENOL Standard Truck SAE 40** is mono grade motor oil for use in truck diesel engines. Also suitable for stationary plants.

## Characteristics

- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts
- Reduced emissions

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	896,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	15,7	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	165,8	DIN 51562-1
Viscosity Index VI		97	DIN ISO 2909
Pourpoint	°C	-24	DIN ISO 3016
Flashpoint	°C	254	DIN EN ISO 2592
tbn	mg KOH/g	13,0	ASTM D2896

All indicated data are approximate values and are subject to the commercial fluctuations.