



RAVENOL Gasmotorenöl SAE 40

Kategorie: Passenger car motor oil

Artikelnummer: 1133105

Viscosity: 40

Oil type: Mineral

Recommendation: 4-Takt Erdgas-, Biogas- und Klärgasmotoren

Application: Industry



RAVENOL Gasmotorenoel SAE 40 is gas engine oil suitable for the lubrication of four stroke gas engines, when gases are used with lower sulphur contents.

Application Note

RAVENOL Gasmotorenoel SAE 40 is suitable to apply in four stroke gas engines for which lower acid neutralisation capacity is required. RAVENOL Gasmotorenoel SAE 40 can be applied when natural gas, biomass gas or sewing gas are used. Application of this motor oil contributes to a longer lifetime and decreased maintenance costs, because longer Service fill times are possible. Due to its lower phosphate content a longer lifetime of the catalyst can be achieved.

20L | 1133105-020

20L | 1133105-B20

60L | 1133105-060

208L | 1133105-208

Characteristics

- Reduction of deposits in the combustion chamber and on the valves
- Good noise reducing properties
- Good oxidation resistance
- Strong acid neutralisation capacity
- Excellent cleaning properties
- Good protection against wear
- Excellent filterability

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		braun	VISUELL
tbn	mg KOH/g	5,5	ASTM D2896
Viscosity at 100 °C	mm ² /s	13,7	DIN 51562-1
Viscosity at 40 °C	mm ² /s	132,0	DIN 51562-1
Viscosity Index VI		108	DIN ISO 2909
Density at 20 °C	kg/m ³	872,0	EN ISO 12185
Flashpoint	°C	274	DIN EN ISO 2592
Pourpoint	°C	-21	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.