



# RAVENOL Schneefräse 4-Takt SAE 5W-30



1L | 1151105-001  
4L | 1151105-004

**Kategorie:** 4 stroke engine oil

**Artikelnummer:** 1151105

**Viscosity:** 5W-30

**Specification:** ACEA A5/B5, API SL, API SM

**Oil type:** Full synthetic

**Recommendation:** Ariens, Briggs&Stratton, Caiman, Canadiana, Craftsman, CubCadet, Honda, Husqvarna, McCulloch, MTD, Murray, Partner, Snapper, Stiga, Swisher, TORO, White Outdoor, Yard-Man

**Application:** Hobby and garden

**RAVENOL Schneefräse 4-Takt SAE 5W-30** is high quality full synthetic green coloured four-stroke engine oil.

**RAVENOL Schneefräse 4-Takt SAE 5W-30** is specially designed for 4-stroke snow blowers. Excellent wear protection also by high pressure, excellent corrosion protection. Because of the noticeable fuel economy **RAVENOL Schneefräse 4-Takt SAE 5W-30** contributes to the reduction of pollutant emissions and protecting the environment.

## Application Note

**RAVENOL Schneefräse 4-Takt SAE 5W-30** is fuel efficient engine oil special conceived for 4-stroke snow blower engines.

## Characteristics

- Fast oiling of the engine, also by low temperatures
- Low oil consumption because of the low evaporation tendency
- Excellent wear protection by high pressure
- Excellent corrosion protection
- Safety towards sludge, coking, leaking and corrosion also in unfavourable operational conditions
- No oil caused deposits in combustion chambers, in piston ring zone and on valves
- Neutrality against seal materials

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	849,0	EN ISO 12185
Colour		grün	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	10,0	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	56,6	DIN 51562-1
Viscosity Index VI		165	DIN ISO 2909
HTHS Viscosity at 150 °C	mPa*s	3,08	ASTM D5481
CCS Viscosity at -30 °C	mPa*s	4300	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	14.000	ASTM D4684
Pourpoint	°C	-39	DIN ISO 3016
Noack Volatility	% M/M	9,4	ASTM D5800
Flashpoint	°C	240	DIN EN ISO 2592
tbn	mg KOH/g	10,9	ASTM D2896
Sulphated Ash	%wt.	1,1	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.