



RAVENOL WATERCRAFT Fullsynth. 2-Takt



1L | 1151210-001
4L | 1151210-004
10L | 1151210-010
20L | 1151210-020
20L | 1151210-B20
60L | 1151210-060
208L | 1151210-208
1000L | 1151210-700

Kategorie: 2 stroke engine oil

Artikelnummer: 1151210

Specification: API TD, ISO L-EGD, JASO FD

Oil type: Full synthetic

Approvals: NMMA TC-W3, RL-29019G

Application: Marine

RAVENOL WATERCRAFT Fullsynth. 2-Takt is high quality blue coloured full synthetic two-stroke engine oil.

RAVENOL WATERCRAFT Fullsynth. 2-Takt with special esters and Polyisobutylene (PIB) and with effectively two stroke additives.

RAVENOL WATERCRAFT Fullsynth. 2-Takt is especially developed for two stroke engines in water vehicles.

Application Note

RAVENOL WATERCRAFT Fullsynth. 2-Takt can generally be mixed with regular petrol 1:100.

RAVENOL WATERCRAFT Fullsynth. 2-Takt is used for lubrication of air-cooled two-stroke petrol engines with very high speed and heaviest load.

RAVENOL WATERCRAFT Fullsynth. 2-Takt is also suitable for the lubrication of two stroke scooters with water cooling.

Characteristics

- A proper lubrication of all engine parts
- A strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from combustion residues and deposits
- Clean spark plugs provide optimal performance of the engines
- A very high wear and corrosion protection
- Low exhaust emission levels by good combustion
- Very low Pourpoint, also to use at very low temperature

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		blau	VISUELL
Viscosity at 100 °C	mm ² /s	10,8	DIN 51562-1
Viscosity at 40 °C	mm ² /s	70,7	DIN 51562-1
Viscosity Index VI		128	DIN ISO 2909
Density at 20 °C	kg/m ³	865,0	EN ISO 12185
Flashpoint	°C	143	DIN EN ISO 2592
Pourpoint	°C	-42	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.