



# RAVENOL SCOOTER 2-Takt Teilsynth.



1L | 1152150-001  
4L | 1152150-004  
10L | 1152150-010  
20L | 1152150-020  
20L | 1152150-B20  
60L | 1152150-060  
208L | 1152150-208  
1000L | 1152150-700

**Kategorie:** 2 stroke engine oil

**Artikelnummer:** 1152150

**Specification:** API TC, ISO L-EGC

**Oil type:** Semi-synthetic

**Approvals:** JASO FC (M049RAV150)

**Recommendation:** Aprilia, Honda, Kymco, Peugeot, Piaggio, Suzuki, Vespa, Yamaha

**Application:** Motorcycle

**RAVENOL SCOOTER 2-Takt Teilsynth.** is high quality semi-synthetic two-stroke engine oil with special esters and Polyisobutylene (PIB) for air- and water cooled two-stroke engines. Suitable for separate lubrication systems and self-mixing systems.

**RAVENOL SCOOTER 2-Takt Teilsynth.** is based on mineral and synthetic base oils with extraordinary effectively two-stroke additives.

## Application Note

**RAVENOL SCOOTER 2-Takt Teilsynth.** is a self-mixing two-stroke oil and suitable for mixed and separat.

**RAVENOL SCOOTER 2-Takt Teilsynth.** is specially used for lubrication of air-cooled two-stroke petrol engines with very high speed and heaviest load.

**RAVENOL SCOOTER 2-Takt Teilsynth.** is also suitable for the lubrication of two-stroke petrol engines with water cooling (e.g. Motorbikes).

**RAVENOL SCOOTER 2-Takt Teilsynth.** can generally be mixed with regular petrol 1:75.

Please follow the manufacturer's recommendations.

## Characteristics

- A proper lubrication of all engine parts
- A strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from combustion residues and deposits
- Clean spark plugs provide optimal performance of the engines
- A very high wear and corrosion protection
- Low exhaust emission levels by good combustion

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		rot	VISUELL
Sulphated Ash	%wt.	0,04	DIN 51575
Viscosity at 100 °C	mm <sup>2</sup> /s	9,7	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	68,4	DIN 51562-1
Viscosity Index VI		122	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	865,0	EN ISO 12185
Flashpoint	°C	168	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.