



RAVENOL WATERCRAFT Teilsynth. 2-Takt



1L | 1152210-001
4L | 1152210-004
10L | 1152210-010
20L | 1152210-020
20L | 1152210-B20
60L | 1152210-060
208L | 1152210-208
1000L | 1152210-700

Kategorie: 2 stroke engine oil

Artikelnummer: 1152210

Specification: API TC, ISO L-EGC, JASO FC

Oil type: Semi-synthetic

Approvals: NMMA TC-W3, RL-30010H

Application: Marine

RAVENOL WATERCRAFT Teilsynth. 2-Takt is a semi-synthetic 2-stroke oil, dyed blue, with special esters and Polyisobutylene (PIB) and an ash-free additive package for optimum viscosity and corrosion protection.

Application Note

RAVENOL WATERCRAFT Teilsynth. 2-Takt can be used in a mixture of up to 1:75 with regular petrol.

RAVENOL WATERCRAFT Teilsynth. 2-Takt is particularly suitable for the lubrication of air-cooled two-stroke petrol engines with high engine speeds and severe loads.

RAVENOL WATERCRAFT Teilsynth. 2-Takt is excellently suited for the lubrication of two-stroke watercrafts with water cooling systems.

RAVENOL WATERCRAFT Teilsynth. 2-Takt meets the requirements of the National Marine Manufacturers' Association NMMA TC-W3 (Yamaha CE 50S, Mercury).

Characteristics

- Excellent lubrication of all engine parts
- A powerful cleaning performance, which keeps combustion chambers as well as intake and exhaust channels free of combustion residue and deposits to the greatest possible extent
- Clean spark plugs provide for an optimum performance of the engine
- Great wear and corrosion protection
- Low vehicle exhaust emission due to good combustion

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		blau	VISUELL
Viscosity at 100 °C	mm ² /s	9,6	DIN 51562-1
Viscosity at 40 °C	mm ² /s	69,9	DIN 51562-1
Viscosity Index VI		117	DIN ISO 2909
Density at 20 °C	kg/m ³	865,0	EN ISO 12185
Flashpoint	°C	168	DIN EN ISO 2592
Pourpoint	°C	-33	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.