



0.1L | 1153100-100  
1L | 1153100-001  
1L | 1153100-D01  
4L | 1153100-004  
10L | 1153100-010  
20L | 1153100-020  
20L | 1153100-B20  
60L | 1153100-060  
208L | 1153100-208  
1000L | 1153100-700

## RAVENOL Selfmix 2T

**Kategorie:** 2 stroke engine oil

**Artikelnummer:** 1153100

**Specification:** API TC, ISO L-EGB, NMMA TC-W

**Oil type:** Mineral

**Approvals:** JASO FB (M049RAV155)

**Recommendation:** Dolmar, Hitachi, Husqvarna, Jonsered, Makita, Maruyama, McCulloch, Oleo-Mac, Oregon, Partner, Poulan, Ryobi, Stihl

**Application:** Motorcycle, Marine, Hobby and garden

**RAVENOL Selfmix 2T** is a premixed mineral lubricant which meets the exacting demands of two-stroke engines. It effectively prevents the accumulation of carbon deposits in the piston, the combustion chambers and the exhaust ports, and is formulated to avoid contamination of spark plugs and corrosion damage to drive mechanism components.

### Application Note

**RAVENOL Selfmix 2T** is specially designed for universal use in motorcycles which have separate lubrication and self-mixing systems. When used in separate lubrication systems this product will ensure optimal lubrication and minimizes smoke to help protect the environment. It is suitable for air-cooled as well as water-cooled two-stroke gasoline engines in motorcycles, mopeds and scooters, as well as for other equipment such as lawnmowers etc.

### Characteristics

- Excellent corrosion protection
- Excellent oxidation stability
- Very high wear protection
- Environmentally friendly with low smoke formulation
- Low coking capabilities
- Formulated for universal use

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	872,0	EN ISO 12185
Colour		rot	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	9,0	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	66,4	DIN 51562-1
Viscosity Index VI		110	DIN ISO 2909
Pourpoint	°C	-24	DIN ISO 3016
Flashpoint	°C	178	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.