



1L | 1153150-001  
4L | 1153150-004  
10L | 1153150-010  
20L | 1153150-020  
20L | 1153150-B20  
60L | 1153150-060  
208L | 1153150-208  
1000L | 1153150-700

# RAVENOL SCOOTER 2-Takt Mineral

**Kategorie:** 2 stroke engine oil

**Artikelnummer:** 1153150

**Specification:** API TC, ISO L-EGB

**Oil type:** Mineral

**Approvals:** JASO FB (M049RAV156)

**Recommendation:** Aprilia, Honda, Kymco, Peugeot, Piaggio, Suzuki, Vespa, Yamaha

**Application:** Motorcycle

**RAVENOL SCOOTER 2-Takt Mineral** is high quality mineral two-stroke engine oil.

**RAVENOL SCOOTER 2-Takt Mineral** is formulated with mineral base oils with effectively additives for optimum protection against wear and prevent corrosion, deposits and auto-ignitions.

**RAVENOL SCOOTER 2-Takt Mineral** is optimized for air- and watercooled two stroke engines.

## Application Note

**RAVENOL SCOOTER 2-Takt Mineral** can generally be mixed with regular petrol 1:50.

**RAVENOL SCOOTER 2-Takt Mineral** is best choice for separate lubrication and self-mixing systems. The use in oil injection systems this product will ensure optimum lubrication and minimizes smoke environmentally friendly.

**RAVENOL SCOOTER 2-Takt Mineral** is used for lubrication of air-cooled two-stroke petrol engines.

**RAVENOL SCOOTER 2-Takt Mineral** is also suitable for the lubrication of two stroke scooters with water cooling. Suitable for separate lubrication systems and self-mixing systems.

## Characteristics

- A proper lubrication of all engine parts
- A strong cleaning effect, for clean combustion chambers. Cleans intake and exhaust ports from combustion residues and deposits
- Clean spark plugs provide optimal performance of the engines
- A very high wear and corrosion protection
- Low exhaust emission levels by good combustion

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		rot	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	9,0	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	66,4	DIN 51562-1
Viscosity Index VI		110	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	872,0	EN ISO 12185
Flashpoint	°C	178	DIN EN ISO 2592
Pourpoint	°C	-24	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.