



1L | 1153200-001
1L | 1153200-D01
4L | 1153200-004
5L | 1153200-005
10L | 1153200-010
20L | 1153200-020
20L | 1153200-B20
60L | 1153200-060
208L | 1153200-208
1000L | 1153200-700

RAVENOL Outboardoel 2T Mineral

Kategorie: 2 stroke engine oil

Artikelnummer: 1153200

Specification: API TC

Oil type: Mineral

Approvals: NMMA TC-W3, RL-90000G

Recommendation: Evinrude, Johnson, Mercury, Selva, Suzuki, Tohatsu, Yamaha

Application: Marine

RAVENOL Outboardoel 2T Mineral is high quality 2-stroke engine oil based on mineral base oils with an ashless additive package for optimum lubricity and excellent corrosion protection.

RAVENOL Outboardoel 2T Mineral is specifically designed for use in fresh water-cooled outboard engines with separate (Auto lube systems) or mixed lubrication.

RAVENOL Outboardoel 2T Mineral meets the requirements of the National Marine Manufacturers Association NMMA TC-W3.

Application Note

RAVENOL Outboardoel 2T Mineral is recommended for "TC-W3" Fluids in all outboard engines according to the prescribed mixing ratio from the engine manufacturer. It can also be used for engines operating in seawater.

RAVENOL Outboardoel 2T Mineral is recommended for use in outboard engines of Yamaha, Suzuki, Tohatsu, Johnson, Evinrude, Mercury und Selva.

Typical mixing ratio: 1:50.

Follow the manufacturer's recommendations!

Characteristics

- An excellent corrosion protection in all oil-wetted engine parts
- An excellent oxidation stability
- High wear protection
- Immediate, homogeneous mixture with the used fuel (including lead-free)
- An effective pressure and temperature resistant oil film
- Environmentally friendly with low smoke
- A clean burning with no deposits

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	866,2	EN ISO 12185
Colour		blau	VISUELL
Viscosity at 100 °C	mm ² /s	7,45	DIN 51562-1
Viscosity at 40 °C	mm ² /s	43,3	DIN 51562-1
Viscosity Index VI		119	DIN ISO 2909
Pourpoint	°C	-24	DIN ISO 3016
Flashpoint	°C	137	DIN EN ISO 2592
Sulphated Ash	%wt.		DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.