



RAVENOL Outboardoel 4T SAE 25W-40



1L | 1153207-001
4L | 1153207-004
10L | 1153207-010
20L | 1153207-020
20L | 1153207-B20
60L | 1153207-060
208L | 1153207-208

Kategorie: 4 stroke engine oil

Artikelnummer: 1153207

Viscosity: 25W-40

Specification: API SM, NMMA FC-W, NMMA FC-W (CAT)

Oil type: Mineral

Approvals: NMMA FC-W CAT, FC-43517X

Recommendation: Evinrude, Honda, Johnson, Mercury Verado, Nissan, Suzuki, Tohatsu, Yamaha

Application: Marine

RAVENOL Outboardoel 4T SAE 25W-40 is a mineral engine oil with a special formulation for 4-stroke outboard engines with injection according to NMMA FC-W and NMMA FC-W (CAT).

RAVENOL Outboardoel 4T SAE 25W-40 offers perfect lubrication and wear protection through special low-ash additives and excellent corrosion protection.

RAVENOL Outboardoel 4T SAE 25W-40 is blue colored high performance 4-stroke motor oil.

RAVENOL Outboardoel 4T SAE 25W-40 is released and thus meets the requirements of the National Marine Manufacturers Association NMMA FC-W (CAT) for use in engines with catalysts.

Application Note

RAVENOL Outboardoel 4T SAE 25W-40 can be used in all outboard motors according to the engine manufacturer's specifications, for which oil is recommended according to FC-W and FC-W (CAT).

RAVENOL Outboardoel 4T SAE 25W-40 can also be used for engines operating in seawater.

RAVENOL Outboardoel 4T SAE 25W-40 meets the requirements from Yamaha 115 General Performance Engine Test for 4-stroke outboard motors.

Follow the manufacturer's recommendations.

Characteristics

- Perfect lubrication of all engine parts
- A strong cleaning effect and a residue-free combustion without deposits
- Good cold start properties
- A very high-wear, oxidation and corrosion protection
- Excellent shear stability
- Corrosion protection in all oil-wetted engine parts
- An adhesive, pressure-and temperature-resistant oil film

- Suitable for Catalysts

Technical Product Data

| PROPERTY | UNIT | DATA | AUDIT |
|---------------------|--------------------|-------|-----------------|
| Colour | | blau | VISUELL |
| tbn | mg KOH/g | 7,2 | ASTM D2896 |
| Viscosity at 100 °C | mm ² /s | 13,6 | DIN 51562-1 |
| Viscosity at 40 °C | mm ² /s | 120,7 | DIN 51562-1 |
| Viscosity Index VI | | 110 | DIN ISO 2909 |
| Density at 20 °C | kg/m ³ | 878,6 | EN ISO 12185 |
| Flashpoint | °C | 262 | DIN EN ISO 2592 |
| Pourpoint | °C | -27 | DIN ISO 3016 |

All indicated data are approximate values and are subject to the commercial fluctuations.