



RAVENOL MARINEOIL DIESEL SHPD SAE 10W-40



1L | 1162100-001
4L | 1162100-004
10L | 1162100-010
20L | 1162100-020
20L | 1162100-B20
60L | 1162100-060
208L | 1162100-208
1000L | 1162100-700

Kategorie: Marine engine oil

Artikelnummer: 1162100

Viscosity: 10W-40

Specification: ACEA B4, ACEA E7, API CF, API CI-4

Oil type: Semi-synthetic

Recommendation: Caterpillar, Detroit Diesel, IVECO, MAN, Mercruiser, MTU, NANNI Diesel, PERKINS, Scania LDF-2, SKL, STEYR, SULZER, VETUS DEUTZ, VOLVO PENTA, Yanmar

Application: Marine

RAVENOL MARINEOIL DIESEL SHPD 10W-40 is a low friction engine oil for the use in marine diesel engines.

RAVENOL MARINEOIL DIESEL SHPD 10W-40 is produced with unconventional and HC basic oils, synthetic components and modern additives.

RAVENOL MARINEOIL DIESEL SHPD 10W-40 guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

Characteristics

- Excellent detergent and dispersant characteristics
- Low evaporation
- High aging stability
- Protection of reflecting surface formation
- Very good cold start characteristics
- Reduces oil and fuel consumption

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		blau	VISUELL
Sulphated Ash	%wt.	1,3	DIN 51575
tbn	mg KOH/g	11,0	ASTM D2896
Viscosity at 100 °C	mm ² /s	13,7	DIN 51562-1
Viscosity at 40 °C	mm ² /s	92,0	DIN 51562-1
Viscosity Index VI		151	DIN ISO 2909
CCS Viscosity at -25 °C	mPa*s	6470	ASTM D5293
Density at 20 °C	kg/m ³	866,0	EN ISO 12185
Flashpoint	°C	214	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.