



RAVENOL MARINEOIL PETROL SAE 10W-40



1L | 1162200-001
4L | 1162200-004
10L | 1162200-010
20L | 1162200-020
20L | 1162200-B20
60L | 1162200-060
60L | 1162200-D60
208L | 1162200-208
1000L | 1162200-700

Kategorie: Marine engine oil

Artikelnummer: 1162200

Viscosity: 10W-40

Specification: API SL

Oil type: Semi-synthetic

Recommendation: Kohler, Mercruiser, VOLVO PENTA AB, Yanmar

Application: Marine

RAVENOL MARINEOIL PETROL 10W-40 is an engine oil for the use in marine gasoline engines.

RAVENOL MARINEOIL PETROL 10W-40 is produced with unconventional and HC basic oils, synthetic components and modern additives.

RAVENOL MARINEOIL PETROL 10W-40 guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

Characteristics

- Excellent detergent and dispersant characteristics
- Low evaporation
- High aging stability
- Protection of reflecting surface formation
- Very good cold start characteristics
- Reduces oil and fuel consumption

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	866,0	EN ISO 12185
Colour		blau	VISUELL
Viscosity at 100 °C	mm ² /s	13,6	DIN 51562-1
Viscosity at 40 °C	mm ² /s	91,8	DIN 51562-1
Viscosity Index VI		150	DIN ISO 2909
CCS Viscosity at -25 °C	mPa*s	6480	ASTM D5293
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	210	DIN EN ISO 2592
tbn	mg KOH/g	11,0	ASTM D2896
Sulphated Ash	%wt.	1,3	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.