



RAVENOL MARINEOIL PETROL SAE 15W-40

RAVENOL MARINEOIL PETROL SAE 15W-40

- 1L | 1163200-001
- 4L | 1163200-004
- 10L | 1163200-010
- 20L | 1163200-020
- 20L | 1163200-B20
- 60L | 1163200-060
- 208L | 1163200-208

Kategorie: Marine engine oil

Artikelnummer: 1163200

Viscosity: 15W-40

Specification: API SL

Oil type: Mineral

Recommendation: Kohler, Mercruiser, VOLVO PENTA AB, Yanmar

Application: Marine

RAVENOL MARINEOIL PETROL SAE 15W-40 is a high additive treated HD engine oil for marine gasoline engines.

RAVENOL MARINEOIL PETROL SAE 15W-40 is especially produced for extended oil change intervals (under consideration of the manufacturer instruction).

Characteristics

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	879,5	EN ISO 12185
Colour		blau	VISUELL
Viscosity at 100 °C	mm ² /s	15,0	DIN 51562-1
Viscosity at 40 °C	mm ² /s	115,7	DIN 51562-1
Viscosity Index VI		134	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	238	DIN EN ISO 2592
tbn	mg KOH/g	10,5	ASTM D2896

All indicated data are approximate values and are subject to the commercial fluctuations.