



# RAVENOL MARINEOIL PETROL SAE 25W-40



1L | 1163220-001  
4L | 1163220-004  
10L | 1163220-010  
20L | 1163220-020  
20L | 1163220-B20  
60L | 1163220-060  
208L | 1163220-208  
1000L | 1163220-700

**Kategorie:** Marine engine oil

**Artikelnummer:** 1163220

**Viscosity:** 25W-40

**Specification:** NMMA FC-W, NMMA FC-W (CAT)

**Oil type:** Mineral

**Approvals:** NMMA FC-W CAT, FC-43514X

**Recommendation:** Evinrude, Honda, Johnson, Kohler, Mercruiser, Mercury, Suzuki, VOLVO PENTA AB, Yamaha, Yanmar

**Application:** Marine

**RAVENOL MARINEOIL PETROL SAE 25W-40** is a modern high additive treated marine engine oil with synthetic additives. It is suitable for inboard and outboard marine gasoline engines. The high additive content guarantees an excellent effect on the detergent, dispersant and anti corrosion characteristics.

**RAVENOL MARINEOIL PETROL SAE 25W-40** is a top quality product with high safety reserves.

**RAVENOL MARINEOIL PETROL SAE 25W-40** is also suitable in engines with catalyts.

## Application Note

**RAVENOL MARINEOIL PETROL SAE 25W-40** is used in boat engines in case the specification SAE 25W-40 is requested.

## Characteristics

- Suitability for catalyts
- Excellent detergent and dispersant characteristics
- Very good cold start characteristics
- A high oxidation stability
- An excellent viscosity temperature behaviour
- An excellent corrosion protection
- High safety reserves
- Reduction of emissions

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	876,0	EN ISO 12185
Colour		blau	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	18,9	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	161,2	DIN 51562-1
Viscosity Index VI		133	DIN ISO 2909
CCS Viscosity at -15 °C	mPa*s	6500	ASTM D5293
Pourpoint	°C	-30	DIN ISO 3016
Flashpoint	°C	241	DIN EN ISO 2592
tbn	mg KOH/g	11,3	ASTM D2896

All indicated data are approximate values and are subject to the commercial fluctuations.