



RAVENOL Motobike 4-T Standard SAE 10W-40



1L | 1173134-001
4L | 1173134-004
20L | 1173134-020
20L | 1173134-B20
60L | 1173134-060
208L | 1173134-208

Kategorie: Motorbike engine oil

Artikelnummer: 1173134

Viscosity: 10W-40

Specification: API SN, JASO MA2

Oil type: Mineral

Approvals: JASO MA2 T903:2016 (M049RAV179)

RAVENOL Motobike 4-T Standard SAE 10W-40 is an engine oil on mineral oil base with excellent additives which was especially produced for 4 stroke motorbikes from year 2001.

With **RAVENOL Motobike 4-T Standard SAE 10W-40** a solid and high loadable engine oil was developed for superior engines of motorbikes with wet- and oil lubricated clutches.

RAVENOL Motobike 4-T Standard SAE 10W-40 has an excellent lubricating film, adhesive capacity and a very good shear stability as well as an excellent cleaning power and a high aging resistance.

Application Note

RAVENOL Motobike 4-T Standard SAE 10W-40 is suitable as an engine oil for all air- and water-cooled 4-stroke motorbikes in case that the viscosity SAE 10W-40 with the specification JASO MA2 is requested. Observe manufacturer's instructions.

Characteristics

- Good shear stability
- Good cold start characteristics
- High oxidation stability
- Stable lubricating film even under heavy load
- Prevention of black sludge formation
- Very good viscosity-temperature behavior
- Optimal function of engine, clutch and gearbox
- High safety reserves, even with boundary lubrication
- Tested and proven additives

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	859,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	14,7	DIN 51562-1
Viscosity at 40 °C	mm ² /s	97,7	DIN 51562-1
Viscosity Index VI		155	DIN ISO 2909
Pourpoint	°C	-39	DIN ISO 3016
Noack Volatility	% M/M	9,1	ASTM D5800
Flashpoint	°C	226	DIN EN ISO 2592
tbn	mg KOH/g	7,0	ASTM D2896
Sulphated Ash	%wt.	0,86	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.