



RAVENOL LHM PLUS Fluid

Kategorie: Car hydraulic oil

Artikelnummer: 1181110

Specification: DIN 51524-2, ISO 7308, PSA Standard B 71 2710

Oil type: Semi-synthetic

Application: Passenger car



RAVENOL LHM PLUS Fluid is special semisynthetic hydraulic fluid especially designed for use in vehicles of the PSA group (Citroen, Peugeot).

Due to its special formulation **RAVENOL LHM PLUS Fluid** has significantly improved low temperature viscosity and fulfils the PSA approval specification.

Application Note

RAVENOL LHM PLUS Fluid is used in vehicles with appropriately marked fluid reservoir for the hydraulic operation or support of braking, steering and suspension functions.

RAVENOL LHM PLUS Fluid is miscible with earlier LHM fluids.

Characteristics

- A low pour point.
- Excellent viscosity behavior at low temperatures.
- An extremely high viscosity index.
- Low viscosity at low temperatures.
- Neutral behavior towards sealing materials.

1L | 1181110-001

4L | 1181110-004

10L | 1181110-010

20L | 1181110-020

20L | 1181110-B20

60L | 1181110-060

208L | 1181110-208

1000L | 1181110-700

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	837,0	EN ISO 12185
Colour		klar, grün	VISUELL
Viscosity at 100 °C	mm ² /s	7,2	DIN 51562-1
Viscosity at 40 °C	mm ² /s	25,3	DIN 51562-1
Viscosity at -40 °C		2600	ASTM D445
Viscosity Index VI		273	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	2200	ASTM D2983
Pourpoint	°C	-63	DIN ISO 3016
Flashpoint	°C	159	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.