



RAVENOL ATF+4 Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1211100

Oil type: Synthetic

Approvals: Chrysler License-No. 40630041 FCA US LLC

Recommendation: Chrysler MS-9602, Fiat 9.55550-AV4, Mopar 68218054GA, Mopar 68218057GA, Mopar 68218058GA

Application: Passenger car



RAVENOL ATF+4® Fluid is a synthetic, licensed automatic transmission fluid ATF with an unique additive package for Fiat-Chrysler, Jeep and Dodge automatic transmission.

RAVENOL ATF+4® Fluid guarantees maximum wear protection in all operating conditions.

RAVENOL ATF+4® Fluid is mixable with all ATF+4®, ATF+2® or ATF+3® transmission oil.

1L | 1211100-001

4L | 1211100-004

10L | 1211100-010

20L | 1211100-020

20L | 1211100-B20

60L | 1211100-060

208L | 1211100-208

Application Note

RAVENOL ATF+4® Fluid is recommended for refilling and fill up automatic transmission oil for Fiat-Chrysler, Dodge, Plymouth, RAM, Jeep and Eagle vehicles with automatic transmission.

RAVENOL ATF+4® Fluid achieves the warranty of FCA US LLC (Fiat Chrysler Automobiles) and is released with Licence-No. 40630041.

RAVENOL ATF+4® Fluid meets the requirements of current and previous standards for Fiat-Chrysler, Dodge, Plymouth, Jeep and Eagle automatic transmission oil.

Characteristics

- Better protection and better performance than ATF+3®
- Extended transmission life
- Reduces maintenance costs
- Better shift quality through a consistent viscosity profile
- Better cold flow properties
- Smooth switching at low temperatures
- Less transmission wear when operating at low temperatures
- Better oxidation stability and thermal stability than the previous ATF+3®
- Longer oil life period
- Lower oil consumption
- Better fuel economy
- Longer oil change intervals (has been tested extensively with oil change intervals of about 160,000 km)

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	845,0	EN ISO 12185
Colour		rot	VISUELL
Viscosity at 100 °C	mm ² /s	7,5	DIN 51562-1
Viscosity at 40 °C	mm ² /s	35,1	DIN 51562-1
Viscosity Index VI		192	DIN ISO 2909
Pourpoint	°C	-63	DIN ISO 3016
Brookfield Viscosity at -40 °C	mPa*s	6.500	ASTM D2983
Flashpoint	°C	198	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.

RAVENOL special transmission fluids are special developments for special gears and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. If you are unsure about the right transmission fluid, ask your workshop or dealership for advice on the transmission type and OEM original number or ask our experts, making sure to state the VIN code (vehicle identification number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH is not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.