



# RAVENOL Multi ATF LVS Fluid

**Kategorie:** Gear oil for automatic transmissions

**Artikelnummer:** 1211145

**Oil type:** Synthetic



**Recommendation:** Aisin Warner AW-1, ATF Shell 3353/ 134/ L12108, BMW ATF 3+, BMW ATF 6, BMW ATF L 12108, BMW ATF M1375.4, Chrysler, Ford MERCON® SP, Honda ATF Type 3.1, Honda DPFII (DPSF), Honda DPSF2 Ultra 4WD Rear, Honda DW-1, Hyundai SPH-IV, Hyundai SP-IV, KIA SP-IV, KIA SP-IV-RR, Land Rover AW -1, Land Rover M1375.4, Mazda ATF FZ, MB 236.12 (A 001 989 45 03 10), MB 236.14, MB 236.15, MB 236.17, Mitsubishi 4031610 ATF Fluid J3, Mitsubishi Dia Queen ATF-PA, Mopar ZF 8 & 9 Speed ATF, Nissan 999MP-MTP10P, Nissan 999MP-MTS00P Matic Fluid S, Nissan ATF Matic P, Renault Matic J6, SsangYong Caltex, SsangYong DSI M11 6-Speed, SsangYong DSI M78 6-Speed, Toyota / Lexus JWS3324, Toyota ATF T-WS, VOLVO 31256774, VOLVO 31256775, VOLVO 31256776, VW TL 52533, VW TL 55005, VW TL 55540, VW TL 60162, ZF LifeguardFluid 6 - 6HP, ZF LifeguardFluid 8 - 8HP, ZF LifeguardFluid 9 - 9HP

**Application:** Passenger car, Truck

**RAVENOL Multi ATF LVS Fluid** is a synthetic multi-function automatic transmission oil ATF based on highly developed synthesis technology for longest change intervals for automatic transmissions and manual transmissions, in torque converters and numerous power steering systems.

**RAVENOL Multi ATF LVS Fluid** is suitable for maximum change intervals in automatic transmissions, steering and clutch systems, hydraulics and power take-offs of cars and commercial vehicles when oil with low viscosity is required.

## Application Note

**RAVENOL Multi ATF LVS Fluid** is a product with a very wide manufacturer coverage and can be used in almost all conventional automatic transmissions with shift groups.

Not suitable for CVT automatic transmissions.

**RAVENOL Multi ATF LVS Fluid** can be used as a refill oil in a wide range of applications to meet the requirements of Ford, GM, Toyota, Honda, Nissan, Hyundai, KIA, BMW, Mercedes, Volvo, VW, Audi and others. It will be used if no suitable original oil or RAVENOL Professional Line oil is available.

Observe the manufacturer's instructions.

## Characteristics

- Very good lubricity even at low temperatures in winter
- A high, stable viscosity index
- Very low pour point
- Very good oxidation stability
- Protection against wear, corrosion and foaming

1L | 1211145-001

4L | 1211145-004

10L | 1211145-010

20L | 1211145-020

60L | 1211145-060

208L | 1211145-208

- Well-coordinated friction properties
- Neutral behavior towards sealing materials
- Neutral behavior due to inhibition against non-ferrous metals

## Technical Product Data

| PROPERTY                       | UNIT | DATA  | AUDIT           |
|--------------------------------|------|-------|-----------------|
| Density at 20 °C               |      | 848   | EN ISO 12185    |
| Colour                         |      | rot   | VISUELL         |
| Viscosity at 100 °C            |      | 5,9   | DIN 51562-1     |
| Viscosity at 40 °C             |      | 29,8  | DIN 51562-1     |
| Viscosity Index VI             |      | 149   | DIN ISO 2909    |
| Brookfield Viscosity at -40 °C |      | 12050 | ASTM D2983      |
| Pourpoint                      |      | -51   | DIN ISO 3016    |
| Flashpoint                     |      | 220   | DIN EN ISO 2592 |
| Copper Strip Test at 121 °C    |      | 1b    | ASTM D130       |

All indicated data are approximate values and are subject to the commercial fluctuations.