



1L | 1221109-001 4L | 1221109-004 10L | 1221109-010 20L | 1221109-020 60L | 1221109-060 60L | 1221109-D60 208L | 1221109-208 208L | 1221109-D28

RAVENOL TDG 75W-110

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1221109

Viscosity: 75W-110

Specification: API GL-4, API GL-5, API MT-1

Oil type: Full synthetic

Approvals: ZF TE-ML 05A (ZF008351), ZF TE-ML 12N (ZF008351), ZF

TE-ML 16F (ZF008351), ZF TE-ML 21A (ZF008351)

Recommendation: DAF, Mack GO-J, Meets the requirements of Scania STO 1:0, MIL-L-2105 D, MIL-PRF 2105 E, SAE J2360, ZF TE-ML 05B, ZF

TE-ML 07A, ZF TE-ML 08, ZF TE-ML 19C, ZF TE-ML 21B

Application: Passenger car, Truck

RAVENOL TDG 75W-110 is full synthetic "Total Drive Line" low viscosity transmission oil.

RAVENOL TDG 75W-110 is designed based on synthetic base oils and specially coordinated additive treatment. This exceeds the needs of today's application requirements.

RAVENOL TDG 75W-110 is oil is developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks.

Application Note

RAVENOL TDG 75W-110 is universal gear oil developed for manual transmissions and hypoid differentials in passenger cars, delivery vans and heavy trucks. This so called "Total Drive Line" oil is as universal product widely usable.

Characteristics

- · Excellent thermal stability.
- High protection from rust, corrosion, foaming.
- Low solidification point.
- Excellent EP properties.
- Good shifting behaviour in low temperatures.
- Extended life.
- Fuel savings.

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m³	874,0	EN ISO 12185
Colour		gelb	VISUELL
Viscosity at 100 °C	mm²/s	21,4	DIN 51562-1
Viscosity at 40 °C	mm²/s	163,5	DIN 51562-1
Viscosity Index VI		155	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	98.700	ASTM D2983
Pourpoint	°C	-45	DIN ISO 3016
Flashpoint	°C	216	DIN EN ISO 2592
Copper Strip Test at 121 °C		1b	ASTM D130

All indicated data are approximate values and are subject to the commercial fluctuations.