



RAVENOL Getriebeoel PSA SAE 75W-80



1L | 1222100-001

4L | 1222100-004

10L | 1222100-010

20L | 1222100-020

20L | 1222100-B20

60L | 1222100-060

60L | 1222100-D60

208L | 1222100-208

208L | 1222100-D28

1000L | 1222100-700

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1222100

Viscosity: 75W-80

Specification: API GL-4

Oil type: Semi-synthetic

Recommendation: PSA B71 2315

Application: Passenger car

RAVENOL Getriebeoel PSA SAE 75W-80 is a high-quality solvent refined base oil based semi-synthetic multi-grade transmission oil with special EP (extreme pressure) properties.

RAVENOL Getriebeoel PSA SAE 75W-80 has a special formula for outstanding wear protection and lubrication properties.

Application Note

RAVENOL Getriebeoel PSA SAE 75W-80 is used in manual shift transmissions requiring trouble-free lubrication.

RAVENOL Getriebeoel PSA SAE 75W-80 can be used in manual transmissions where the manufacturer specifies a low-viscosity oil.

Characteristics

- Outstanding oxidation protection.
- Low viscosity in low temperatures.
- Excellent wear protection.
- Enhanced EP properties.
- Good foaming properties.
- Neutral to sealants.
- Outstanding protection from rust and corrosion.

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	843,0	EN ISO 12185
Colour		hellbgebl	VISUELL
Viscosity at 100 °C	mm ² /s	8,5	DIN 51562-1
Viscosity at 40 °C	mm ² /s	43,1	DIN 51562-1
Viscosity Index VI		178	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	52.500	ASTM D2983
Pourpoint	°C	-39	DIN ISO 3016
Flashpoint	°C	234	DIN EN ISO 2592
Copper Strip Test at 121 °C		1b	ASTM D130

All indicated data are approximate values and are subject to the commercial fluctuations.