



RAVENOL Getriebeoel TSG SAE 75W-90



1L | 1222101-001
4L | 1222101-004
10L | 1222101-010
20L | 1222101-020
20L | 1222101-B20
60L | 1222101-060
60L | 1222101-D60
208L | 1222101-208
208L | 1222101-D28
1000L | 1222101-700

Kategorie: Gear oil for manual transmissions and drive axis

Artikelnummer: 1222101

Viscosity: 75W-90

Specification: API GL-4

Oil type: Synthetic

Recommendation: Ford M2C-175, Opel/GM B0401043, VW 501 50, VW G 052 911 A2, VW G 060 726 A2

Application: Passenger car, Truck

RAVENOL Getriebeoel TSG SAE 75W-90 is a synthetic multi-purpose transmission oil for maximum duty manual transmissions.

RAVENOL Getriebeoel TSG SAE 75W-90 is designed based on high-quality synthetic base oils with special additive treatment and inhibition coordinated to the increased stress on manual transmission oils and ensuring trouble-free transmission function.

Application Note

RAVENOL Getriebeoel TSG SAE 75W-90 is suitable for highly stressed manual transmissions (with and without synchronising), transfer cases and steering gearboxes in vehicles and work machines.

Characteristics

- excellent ageing resistance
- extra high pressure absorption properties
- optimal viscosity-temperature properties
- excellent low temperature properties
- shearing stability
- stable lubricating film even under high stress
- extremely low pour point
- good elastomer compatibility to prevent leaks

Technical Product Data

| PROPERTY | UNIT | DATA | AUDIT |
|--------------------------------|--------------------|----------|--------------|
| Density at 20 °C | kg/m ³ | 837,5 | EN ISO 12185 |
| Colour | | hellgelb | VISUELL |
| Viscosity at 100 °C | mm ² /s | 15,7 | DIN 51562-1 |
| Viscosity at 40 °C | mm ² /s | 95,7 | DIN 51562-1 |
| Viscosity Index VI | | 176 | DIN ISO 2909 |
| Brookfield Viscosity at -40 °C | mPa*s | 88.700 | ASTM D2983 |
| Pourpoint | °C | -42 | DIN ISO 3016 |
| Copper Strip Test at 121 °C | | 1b | ASTM D130 |

All indicated data are approximate values and are subject to the commercial fluctuations.