



# RAVENOL Scooter Gear Oil SAE 80W-90



0.12L | 1222202-120

**Kategorie:** Gear oil for manual transmissions and drive axis

**Artikelnummer:** 1222202

**Viscosity:** 80W-90

**Specification:** API GL-4, API GL-5, MIL-L-2105 D, SAE 80W-90

**Oil type:** Synthetic

**Application:** Motorcycle

**RAVENOL Scooter Gear Oil SAE 80W-90** is a synthetic-based scooter gear oil with special effective high-pressure additives for manual transmissions. High load-carrying capacity guarantees optimum gearbox lubrication even at high temperatures.

**RAVENOL Scooter Gear Oil SAE 80W-90** ensures a strong oil film for lubrication even under the most extreme dynamic conditions.

**RAVENOL Scooter Gear Oil SAE 80W-90** reduces friction, prevents wear and corrosion.

## Application Note

**RAVENOL Scooter Gear Oil SAE 80W-90** is suitable for use in manual transmissions for 2- and 4-stroke scooters if an oil according to SAE 80W-90 API GL-5 with EP (Extrem Pressure) properties is specified.

**RAVENOL Scooter Gear Oil SAE 80W-90** has a specially developed packaging for final drives. The content of a tube is usually sufficient for a gear oil change. Observe manufacturer's instructions!

## Characteristics

- High pressure stable lubrication film, thus outstanding wear protection under any stress
- Excellent oxidation stability, no foaming
- Extraordinary ageing stability
- Excellent viscosity-temperature properties
- Effective wear protection
- Extraordinary corrosion protection, no rust, won't harm non-ferrous metals
- Neutral to sealants, transmissions stay tight, no oil loss

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	877,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	14,7	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	131,8	DIN 51562-1
Viscosity Index VI		111	DIN ISO 2909
Pourpoint	°C	-33	DIN ISO 3016
Flashpoint	°C	218	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.