



1L | 1233100-001
4L | 1233100-004
10L | 1233100-010
20L | 1233100-020
20L | 1233100-B20
60L | 1233100-060
60L | 1233100-D60
208L | 1233100-208
1000L | 1233100-700

RAVENOL MARINE Gear Lube

Kategorie: Marine-Getriebeöl

Artikelnummer: 1233100

Specification: API GL-5, SAE 80W-90

Oil type: Mineral

Recommendation: Mercruiser, OMC, VOLVO PENTA, Yanmar

Application: Marine

RAVENOL MARINE Gear Lube contains high-quality base oils, with a balanced combination of additives. This guarantees a high load carrying capacity, wear protection and oxidation stability.

Due to its balanced formulation **RAVENOL MARINE Gear Lube** offers a good viscosity-temperature behavior, low pour point and no foaming.

RAVENOL MARINE Gear Lube allows use with different operating conditions.

Application Note

RAVENOL MARINE Gear Lube is gear oil for lubricating in boat and ship transmissions, when a GL-5 transmission type is required.

Characteristics

- Good adhesion and pressure-resistant lubricating film
- Excellent oxidation stability
- Very good viscosity-temperature behaviour
- Wear-resistant effect
- No foaming tendency
- Extraordinary ageing stability
- A neutral behaviour towards metals and sealing materials

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	882,0	EN ISO 12185
Colour		blau	VISUELL
Viscosity at 100 °C	mm ² /s	14,3	DIN 51562-1
Viscosity at 40 °C	mm ² /s	130,3	DIN 51562-1
Viscosity Index VI		108	DIN ISO 2909
Brookfield Viscosity at -26 °C	mPa*s	60.100	ASTM D2983
Pourpoint	°C	-33	DIN ISO 3016
Flashpoint	°C	222	DIN EN ISO 2592
Copper Strip Test at 121 °C		1b	ASTM D130

All indicated data are approximate values and are subject to the commercial fluctuations.