



180L | 1340106-180

# RAVENOL Amber Getriebefließfett

**Kategorie:** Grease

**Artikelnummer:** 1340106

**Specification:** DIN 51502: GP0K-30, ISO 6743-9: ISO-L-XCCFB0

**Application:** Passenger car, Truck, Agricultural machinery

**RAVENOL Amber Getriebefließfett** is a high-quality lithium saponified multi-purpose grease based on highly viscous paraffinic base oils with EP additives, which do not contain heavy metals or chlorine.

## Application Note

**RAVENOL Amber Getriebefließfett** is particularly suitable for lubrication under the following unfavourable conditions: High surface pressure, irregular impact loads, wet conditions, soiling.

**RAVENOL Amber Getriebefließfett** is used in central lubrication systems of truck trailers.

**RAVENOL Amber Getriebefließfett** is also used for the lubrication of heavy duty roller and ball bearings in the industrial sector, mainly for low speeds.

## Characteristics

- Excellent EP effect and wear protection
- Outstanding oxidation and corrosion protection even in the presence of moisture
- Very good mechanical stability
- Excellent resistance to water
- Long service life and therefore, longer lubrication intervals possible
- Excellent resistance to ageing
- Good pumpability, even at low temperatures

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		braun	VISUELL
Thickener		Lithium-Komplexseifen	DIN 51757
NLGI-Class		0	DIN 51818
Product Classification		GP0K-30	DIN 51502
Working Temperature	°C	-30 / +120	DIN 51825
Short term temperature up to	°C	120	DIN 51757
Worked Penetration at 60 Strokes	mm/10/25°C	355-385	ISO 2137
Corrosion (SKF Emscor dist. Water)	Korr. Grad	1	DIN 51802
Dropping Point	°C	185	DIN ISO 2176
Copper Corrosion (24h/120 °C)		1	DIN 51811
Water Resistance (3h/90 °C)	°C	1-90	DIN 51807-1
VKA Pressure Carrying Capacity	N	unter 2000	DIN 51350-4
Kinematic Viscosity (Base Oil) at 40 °C	mm <sup>2</sup> /s	65	DIN 51562-1

All indicated data are approximate values and are subject to the commercial fluctuations.